



### FEATURES:

- ✓ High temperature insulation material for use up to +428°F, (+220°C).
- ✓ Mounts in panels from .070" to .375" (1.60mm to 9.53mm).
- ✓ Mates with Pomona's MDP and all standard double banana plugs.
- ✓ Ideal for mounting to panels or chassis boxes.

### MATERIALS:

*Banana Jack Insulation:* Polyphenylene Sulfide Molded to Banana Jack Bodies, Color Blue and Black

*Mounting Plate:* Polyphenylene Sulfide, Color Black

*Insulator:* Polyphenylene Sulfide

*Hex Nut:* 3/8" 1/4-32: Nickel Plated Brass

*Lockwasher:* 1/4 Internal Tooth, Nickel Plated Steel

*Banana Jack Body/Solder Turret:* Brass, H.H. per QQ-B-626, Alloy 360, 1/2 Hard.

*Finish, Banana Jack Body/Solder Turret:* Bright tin plated per MIL-T-10727.

### RATINGS:

**Operating Voltage:** Hands free usage in controlled voltage environments: 2500 Vrms maximum. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

**Current:** 15 Amperes

**Operating Temperature:** +428°F (+220°C).

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

**ORDERING INFORMATION:**

Model: 5233-0 (Black base with one black and one blue banana jack)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).  
All specifications are to the latest revisions. Specifications are subject to change without notice.  
Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)